



iThick-200

Ultrasonic Thickness Gauge



Video



Contact us

Mikrosize Precision Instrument Co.,Ltd

A-4035 RuiFeng Business Expo, Wuhu City, China , 241000.

Web:www.mikrosize.com

Email:mikrosize@mikrosize.com

Web:www.mikrosize.com

Email:mikrosize@mikrosize.com



Product Features and Application

Product Features

- Utilizes both Interface Echo-to-backwall Echo Differential (IE) and Pulse-Echo (PE) ultrasonic principles, providing PE, IE, and TEST measurement modes for accurate thickness gauging through coatings.
- Display resolution of 0.01 mm with a measurement error limit of $\pm 0.4\%H$ (H = workpiece thickness), ensuring high precision for demanding applications.
- Offers zero calibration and velocity calibration; automatically corrects systematic errors and determines material velocity from a known-thickness reference block.
- Stores complete measurement data—thickness value, sound velocity, and time stamp—up to 500 data groups. High-contrast LCD with LED backlight clearly displays thickness, coupling status, battery level, calibration state, velocity, time, etc., under any lighting conditions.
- Powered by two AA alkaline batteries, providing up to 5 hours of continuous operation (backlight off) with real-time battery indicator.
- Auto-power-off after 2 minutes (adjustable) of inactivity; manual power switch also provided for user convenience.
- Configurable settings: unit system (metric/imperial), scan mode (on/off), beep, flashing alarm, probe parameters, factory reset, data export to PC, file deletion, contrast, system time, standby time, and firmware version display—meeting diverse user needs.

Application

- Purity verification: employs ultrasonic testing to detect adulteration inside gold and silver bars, coins, and other precious metals, accurately determining their fineness.
- Precise thickness measurement of plates made from various materials—steel, non-ferrous metals, etc.—across different ranges:
 - Standard mode: 1–300 mm (steel)
 - Cast-iron mode: 4–508 mm
 - Precision mode: 0.75–35 mm
 - High-temperature mode: 4.0–80 mm




Instrument Interface



- 1. Power / Backlight**
- 2. Menu**
- 3. Velocity**
- 4. Enter / Confirm**
- 5. Calibrate**
- 6. Store**
- 7. Light Source Port**
- 8. Up Arrow**
- 9. Down Arrow**
- 10. Reference Block**

Button Function



**1. Current File Number
5. Sound Velocity Unit**

**2. Measurement Mode
6. Battery Level**

**3. Menu Option
7. Coupling Indicator**

**4. Time
8. Displayed Value**

System Settings

Language: ENGLISH
Units: METRIC
Scan Mode: OFF
SELECT ↓DOWN

Language: ENGLISH
Units: METRIC
Scan Mode: OFF
SELECT ↑UP ↓DOWN

Language: ENGLISH
Units: METRIC
Scan Mode: OFF
SELECT ↑UP ↓DOWN

- Within the menu interface, users can configure:

- Language: Chinese, English, or Spanish
- Unit system: Metric or Imperial
- Scan mode

- Scan Mode:

In this mode, the instrument continuously updates and displays the real-time thickness value, allowing uninterrupted measurement while the probe is kept in contact with the workpiece.

Unidad: METRICA
Modo scan: APAG
Sonido: APAG

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Sonda: 5M
Modo scan: APAG
Sonido: APAG

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG

Sonido: APAG

Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

Modo scan: APAG
Sonido: APAG
Flash LED: ENC

- Users can configure:

- Beep and Flash Alarm: Enable or disable audible beep and visual flash alerts while in measurement mode.
- Probe Selection: Choose the appropriate probe model.
- Resolution: Set the measurement resolution to Low, Medium, or High.

Test Mode



- PE (Pulse-Echo):Based on the pulse-echo ultrasonic principle, suitable for measuring the thickness of any material through which ultrasound can propagate at a constant velocity and from which a clear back-wall echo can be obtained.
- IE (Interface-Echo):Uses the difference in sound-path time between the interface echo and the back-wall echo; it can penetrate coatings (coating thickness < 1 mm) to provide an accurate thickness reading of the substrate.
- TEST: Employs ultrasonic technology to detect internal adulteration and determine the purity of precious metals; primarily used for verifying gold bars, silver bars, coins, and other bullion products.



Technical Specification

Working Principle	Ultrasonic
Traversed Coating	IE Mode Can Traverse Through 1500um Coating
Measuring Mode	PE/IE
Measuring Range	0.75~300mm
Precision	$H < 10\text{mm} \pm 0.05\text{mm}$ $H \geq 10\text{mm} \pm (0.05\text{mm} + H/100)\text{mm}$
Probe Size	Standard Delivery 10mm
Resolution	0.1/0.01mm Optional
Touch Screen	2.0 " FSTN, 128 * 64 Dot Matrix, LED Backlight
Measuring Material	Steel, Iron, Glass, Plastic, Aluminum, Etc
Sound Velocity	1000~9999m/s
Storage	500 Groups Of Data
Measuring Unit	Metric/Imperial
Language	English Or Other Customized Languages
Working Temperature	0~50°C
Ambient Humidity	Relative Humidity Less Than 90%
Power Supply	2*1.5V AA Battery
Product Dimensions	150*71*33mm
Net Weight	160g



Packing List

Item	Qty
Main Unit	1 unit
Probe	1 pc
Couplant	1 bottle
Dry Battery	2 pcs
Instrument Case	1 case
Documents	1 set