

Mikrosize®

uRocky-DN

Dolphin Nose Rockwell Hardness Tester



Video



Web: www.mikrosize.com

Email: mikrosize@188.com

Product Feature&Application

Product Features

- Extended horizontally designed indenter can test the parts that are unable to be measured by general hardness tester, such as ring and tube, with the minimum test inner diameter of 25mm.
- Closed loop control system, high precision load cell in stead of dead weights, working directly after connecting with electric power.
- Touch screen for user directly select the hardness scale, test force and displays hardness value, conversion scale, test force, dwell time, etc.
- Semi-automatic type, initial test force loading manually, then main force loading by motor (loading main force, dwell, unload automatically), greatly improved working efficiency.
- With all kinds of rockwell hardness scales HRA HRB HRC etc and high resolution 0.1HR.
- Automatic correction of high, medium and low hardness value on touch screen.
- Automatic correction of load, with the force accuracy increased by dynamometer.
- Automatically apply the initial test force and the main test force.
- Automatic testing process: Automatic loading - Dwell - Unloading, and automatic display hardness value.
- Curve display: test force, displacement depth change curve, real-time test force value curve.
- Powerful data processing function, including: HR, HB, HV and other hardness scale conversion.
- Qualified range can be set, automatic alarm over the limit, tester's name, sample name and other information can be input.
- Operator can set up a password for the machine to protect setup parameters. Safely keep test information and setted parameters.
- With USB interface, test data can be saved in U-flash directly in Excel format. easy to edit and process.
- Machine adopted modular design, easy maintenance.



uRocky-150DN



uRocky-45DN



uRocky-150/45DN

Product Application

- Industrial production, Inspection of product quality on processing technology. Ferrous and nonferrous metals, Hardened steel, tempered steel, annealed steel, hardened steel, sheet of various thicknesses, carbide materials, powder metallurgy materials, hardness and thermal spray coating.
- Dolphin Nose Indenter (Nose mounted indenter) allows access to awkward to reach test points:
 - 1) Ring shape material
 - 2) Tubular material
 - 3) Screw corner
 - 4) Bearing corner, etc.



Operation Interface

Tester

Product Name

Radius of Curvature

Acceptable Range to

Hardness Type

Conversion Type

Dwell Time

Conversion Value

Hardness Value

Displacement Initiation

Calibration

Reset

Main Interface

Calibration

Scale

LowMiddleHigh

Standard

Measured

SaveTest Force

Return

Hardness Calibration

Force Calibration

Standard: kg

Measured: kg

EnterReturn

Force Calibration

Measurement Scale

HR15N/DHR30N/DHR45N/D

HR15T/1.588HR30T/1.588HR45T/1.588

HR15W/3.175HR30W/3.175HR45W/3.175

HR15X/6.35HR30X/6.35HR45X/6.35

HR15Y/12.7HR30Y/12.7HR45Y/12.7

Please choose the right indenter for the scale you choosed.
Explanation

HRA/60/DHR15N/D

Scale/Force/IndentorScale/Force/Indentor

Return

uRocky-150DN

Measurement Scale

CalibrationHRB/100/1.588HRC/150/DHRD/100/D

HRE/100/3.175HRF/60/1.588HRG/150/1.588HRH/60/3.175

HRK/150/3.175HRL/60/6.35HRM/100/6.35HRP/150/6.35

HRR/60/12.7HRS/100/12.7HRV/150/12.7

Please choose the right indenter for the scale you choosed.
Explanation

HRA/60/D

Scale/Force/Indentor

Return

uRocky-45DN

Measurement Scale

CalibrationHRB/100/1.588HRC/150/DHRD/100/D

HRE/100/3.175HRF/60/1.588HRG/150/1.588HRH/60/3.175

HRK/150/3.175HRL/60/6.35HRM/100/6.35HRP/150/6.35

HRR/60/12.7HRS/100/12.7HRV/150/12.7

Please choose the right indenter for the scale you choosed.
Explanation

HRA/60/DHR15N/D


Scale/Force/IndentorScale/Force/Indentor

Return

uRocky-150/45DN



Detailed Photos





Data Output



USB Interface



USB Interface

Machine Real Photo at Factory



Ordering Information



uRocky-150DN Dolphin Nose Rockwell Hardness Tester
uRocky-45DN Dolphin Nose Superficial Rockwell Hardness Tester
uRocky-150/45DN Dolphin Nose Twin Rockwell Hardness Tester



Technical Specification

Model	uRocky-150DN	uRocky-45DN	uRocky-150/45DN
Product Name	Dolphin Nose Rockwell Hardness Tester	Dolphin Nose Superficial Rockwell Hardness Tester	Dolphin Nose Twin Rockwell Hardness Tester
Initial Test force (error < 0.5%)	10Kgf(98.07N)	3.0kgf(29.4N)	Rockwell: 10Kgf(98.07N)
			Superficial Rockwell: 3.0kgf(29.4N)
Total Test force (error < 0.5%)	60kgf(588N) 100kgf(980N) 150kgf(1471N)	15kgf (147.1N) 30kgf (294.2N) 45kgf (441.3N)	Rockwell: 60kgf(588N) 100kgf(980N) 150kgf(1471N)
			Superficial Rockwell: 15kgf (147.1N) 30kgf (294.2N) 45kgf (441.3N)
Hardness Scale	HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRH, HRK, HRL, HRM, HRR, HRP, HRS, HRV	15N, 15T, 15W, 15X, 15Y, 30N, 30T, 30W, 30X, 30Y, 45N, 45T, 45W, 45X, 45Y	Rockwell: HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRH, HRK, HRL, HRM, HRR, HRP, HRS, HRV
			Superficial Rockwell: 15N, 15T, 15W, 15X, 15Y, 30N, 30T, 30W, 30X, 30Y, 45N, 45T, 45W, 45X, 45Y
Conversion Scale	HRA, HRB, HRC, HRD, HRF, HV, HK, HBW, HR15N, HR30N, HR45N, HR15T, HR30T, HR45T		
Hardness Range	HRA:20-88, HRB:20-100, HRC:20-70, HRD:40-77, HRE:70-100, HRF:60-100, HRG:30-94, HRH:80-100, HRK:40-100, HRL:100-120, HRM:85-115, HRR:114-125	HR15N: 70-94, HR30N: 42-86, HR45N: 20-77, HR15T: 67-93, HR30T: 29-82, HR45T: 10-72	Rockwell: HRA:20-88, HRB:20-100, HRC:20-70, HRD:40-77, HRE:70-100, HRF:60-100, HRG:30-94, HRH:80-100, HRK:40-100, HRL:100-120, HRM:85-115, HRR:114-125
			Superficial Rockwell: HR15N: 70-94, HR30N: 42-86, HR45N: 20-77, HR15T: 67-93, HR30T: 29-82, HR45T: 10-72
Executive Standards	BSEN 6508, ISO 6508, ASTM E18, GB/T230		
Dwell time	0-99s		
Hardness resolution	0.1 HR		
Data Display	Touch LCD		
Data Save	The measured values are saved on USB flash drive in Excel format		
Test Height	300mm		
Test Throat	250mm		
Machine Dimension	720 * 260 * 840 mm		
Net Weight	80kg		
Power Supply	AC220 + 5%, 50 ~ 60 hz		

Mikrosize®

Packing List

uRocky-150DN

Item	Qty	Item	Qty
Diamond Rockwell Indentor	1	Diameter 1.5875mm ball head	1
Regulating Screw	4	150mm Test Anvil	1
HRC High Hardness Block	1	55mm Test Anvil	1
HRC Low Hardness Block	1	40mm V-shaped Test Anvil	1
HRB Hardness Block	1	USB Flash Disk	1
Power Line	1	Touch Pen	1
Product Certificate	1 copy	Instruction Manual	1 copy
2A Fuse	2	Dust-proof Plastic Cover	1

uRocky-45DN

Item	Qty	Item	Qty
Diamond Rockwell Indenter	1	1.5875 mm Ball Indenter	1
Regulating Screw	4	150mm Test Anvil	1
HR15N Hardness Block	1	55mm Test Anvil	1
HR30N Hardness Block	1	40mm V-type Test Anvil	1
HR30T Hardness Block	1	Dust-proof Plastic Cover	1
Power Line	1	Instruction Manual	1 Copy
USB Flash Disk	1	Product Certificate	1 Copy
Touch Pen	1	2A Fuse	2

uRocky-150/45DN

Item	Qty	Item	Qty
Diamond Rockwell Indentor	1	1.5875mm Ball Indentor	1
Regulating Screw	4	150mm Test Anvil	1
Hardness Block (HRC high and low, HRB)	3	55mm Test Anvil	1
Hardness Block (HR15, HR30N, HR30T)	3	40mm V-type Test Anvil	1
2A Fuse	2	V-shaped Test Anvil	1
USB Flash Disk,	1	Dust-proof Plastic Cover	1
Power Line	1	Product Certificate	1
Touch Pen	1	Instruction Manual	1



HRB Hardness Block



HRC Hardness Block(High)



HRC Hardness Block(Low)



150mm Flat Test Anvil



55mm Flat Test Anvil



40mm V-shape Test Anvil



Superficial Rockwell Block



USB Flash Disk



Touch Pen